

NSW Weighing Indicator

General Specifications

• Display	52mm digit LCD display, with white LED backlight
• Keyboard	7 keys (Mechanical switch)
• Housing	SST
• Max. Divisions	6,000e; 30,000d
• Load cell excitation voltage	5V/150mA
• ADC update	≤1/10 second
• Operating Temp.	-10°C~+40°C
• Power	AC adapter (12V/500mA), rechargeable battery (6V/4Ah)
• Gross weight	3.5kg
• Packing	Master carton packing, dimension 0.013m ³ Master carton 4 in 1 packing, dimension 0.062m ³



- Easy to use front panel configuration
- Applications: 1. Accumulation 2. Check weighing 3. Net/gross shift
4. Weighing unit conversion 5. Peak hold 6. Animal weighing
- OIML approval from DANAK (approval no.0200-NAWI-04376)
- Keyboard lock function
- Optional RS-232 interface
- Optional analog output (0-10V/4-20mA)
- Optional setpoint output (HI/OK/LOW/BEEP)
- Optional bluetooth

NSW Weighing Indicator

Model Name	Capacity	Readability	Division	Approx. weight	Approval
NSW	X	X	30,000d	3kg	CE
NSW-M	X	X	6,000e	3kg	CE, OIML

Options



Dimensions(mm)

